



Breather Flange Adaptors

Model ABF, ABF-A

Specifications

- Maximum flow rate 576 GPM, 68 CFM @.18 PSI
- Cast aluminum flange
- For use with Lenz CP-752 or CP-1282 elements
- Operating temperature -22F to +212 F (-30C to +100C)
- Compatible with petroleum, mineral, water based fluids
- Cork-rubber gaskets and hardware shipped with adaptor
- All Lenz filler baskets will work with the adaptor
- ABF-A-12 S.A.E (1½"-16 thread) fill port



ABF-752



ABF-752-A

Dimensional Detail

MODEL	ELEMENT THREAD	FILL PORT		A	B	C	D	E	F	G BOLT CIRCLE	H	I	J
ABF-752	1"-12 UNF	—	in	0.6	1.0	2.2	—	—	—	2.8	3.3	0.6	1.9
		—	mm	15.0	25.0	57.0	—	—	—	71.5	84.0	15.0	47
ABF-1282	1½"-16 UNF	—	in	1.0	0.8	2.1	—	—	—	2.8	3.3	0.6	2.0
		—	mm	25	21.5	53.5	—	—	—	71.5	84.0	15.0	50
ABF-752-A8	1"-12 UNF	S.A.E.-8	in	0.6	0.7	4.2	2.1	1.4	1.8	2.8	3.3	—	—
			mm	15	18.0	105.5	54.0	35.0	46.5	71.5	83.0	—	—
ABF-1282-A8	1½"-16 UNF	S.A.E.-8	in	1.0	0.7	4.2	2.1	1.4	1.8	2.8	3.3	—	—
			mm	25	18.0	105.5	54.0	35.0	46.5	71.5	83.0	—	—
ABF-752-A12	1"-12 UNF	S.A.E.-12	in	0.6	0.7	4.2	2.1	1.4	1.8	2.8	3.3	—	—
			mm	15	18.0	105.5	54.0	35.0	46.5	71.5	83.0	—	—
ABF-1282-A12	1½"-16 UNF	S.A.E.-12	in	1.0	0.7	4.2	2.1	1.4	1.8	2.8	3.3	—	—
			mm	25	18.0	105.5	54.0	35.0	46.5	71.5	83.0	—	—

