



Hollow Hex Head Plugs

TCNB

Specifications

- PA 66 with 30% fiberglass low profile threaded plug
- Operating temperature 212°F (100°C)
- FASIT 202 fiber gasket
- BSSP or metric threads standard

Options Available

- Rubber gasket
- Operating temperature 250°F (120°C)
- 50% reinforced fiberglass
- Other metric threads available consult factory



Dimensional Detail

Model	F Port Thread		Ch	D	h1	h2	Torque
TCNB-14	1/4" BSPP	in.	0.24	0.71	0.12	0.31	3
		mm	6	18	3.0	8.0	4
TCNB-38	3/8" BSPP	in.	0.31	0.89	0.14	0.41	5
		mm	8	23	3.5	10.5	7
TCNB-12	1/2" BSPP	in.	0.39	1.10	0.16	0.39	7
		mm	10	28	4.0	10.0	9
TCNB-34	3/4" BSPP	in.	0.47	1.38	0.16	0.41	8
		mm	12	35	4	10.5	11
TCNB-1415	M14 X 1.5	in.	0.24	0.79	0.10	0.35	3
		mm	6	20	2.5	9	4
TCNB-1615	M16 X 1.5	in.	0.31	0.89	0.14	0.41	5
		mm	8	22.5	3.5	10.5	7
TCNB-1815	M18 X 1.5	in.	0.39	1.02	0.12	0.39	6
		mm	10	26	3	10	8
TCNB-2015	M20 X 1.5	in.	0.39	1.10	0.14	0.41	6
		mm	10	28	3.5	10.5	8
TCNB-2215	M22 X 1.5	in.	0.39	1.10	0.14	0.41	6
		mm	10	28	3.5	10.5	8
TCNB-2615	M26 X 1.5	in.	0.47	1.38	0.12	0.45	8
		mm	12	35	3	11.5	11

