



Super Filler Cap Assembly Model FCS-1303 Non Vent Series

Specifications




- Steel shell nickel chrome
- 4.94" diameter bolt circle
- Tether chain standard
- 4.5" hole in tank required for basket
- Cork-rubber gaskets standard
- 8/32 x 1/2" thread forming screws standard
- Operating temperature -22°F to +212°F (-30°C to +100°C)
- Compatible with petroleum and mineral based fluids
- Steel zinc plated mounting flange

Options

- 4.38" 24 or 60 mesh SS baskets
- Vented cap (.128 hole)
- Add LC for Locktabs



**FCS-1303-70 /
FCS-1303-24
Assembly**



1303-8



1303-60



LC-FCS-1303-70

FSC - Assembly Ordering Code

FSC - 1303 - 70 - 1.5 HN

Series		Bayonet		Baskets		Options	
FCS	non locking	1303	Bayonet	24	20 Mesh Screen	1.5 HN	1.5" High Neck
LC-FCS	locking			70	60 Mesh Screen	V	Vented

Dipstick minimum 25 pcs.

Components

Model	Description
1303-8	Gasket (2 required)
1303-24 M	20 mesh replacement screen
1303-70 M	60 mesh replacement screen
FCS-1303	Non vent cap with chain
FCS-1303-CAPFLANGE	Non vent cap, flange, gasket chain
FCS-1303-NV-LCH	Non vent cap, less chain
FCS-1303-V	Vent cap with chain
1309	Flange screws
1303NV-LC	Non vent locking cap, chain

Super Filler Necks Model FCS-1303 Necks

Specifications


- 18 gauge plain steel
- 1.5" weld flange
- 2.5" high neck flange



1303-2.5HN



1303-150



FCS-1303-2.5HN FCS-1303-150

See Technical Bulletin TB.TA22.708 for further information at (Technical Data - www.lenzinc.com).