



Connector type **MLCA 800225**

M8 female connector with molded PVC cable

Description	
Connector angle	straight 180°
Protection rating	IP69K
Dimensions (mm)	
PIN configuration	
Cable diameter (mm)	3
Cable material	PVC (CEI2022)
Lead cross section	0.25 mm ² (AWG 24)
Number of leads	2
Cable length (m)	2.5
Operating temperature (°C)	-25 + 75

Axial female connector with M8 lock nut, 2 pins, round PVC cable, length 2.5 m or 8 feet



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LENZ INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LENZ INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL: ±
 ANGULAR: MACH ± BEND ±
 TWO PLACE DECIMAL ±
 THREE PLACE DECIMAL ±

DRAWN	NAME	DATE
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:

FINISH
 DO NOT SCALE DRAWINGS

DESIGNED FOR:

DESCRIPTION:

SIZE DWG. NO.

A MLCA 8002225 cable assy

REV

SCALE: 1:2 WEIGHT: SHEET 1 OF 1

5 4 3 2 1