



Lenz "AN-WB" Weld Bushings

Lenz "AN-WB" Weld Bushings are designed and machined with a resessed pilot hole opening for welding flush during welding phase to the outside of the tank (the female S.A.E. "O-Ring" connection on top or side of the tank, and the female N.P.T. connection on the inside of the tank) to save time and labor when installing components or accessories, (examples: S.A.E. hydraulic fittings to suction strainers or a return line diffuser) for a leak-free installation.


Lenz "AN-WB" Weld Bushings are precision machined from steel (stainless Steel Optional), unplated, but oiled to prevent corrosion. Available in nine sizes from stock.

AN-WB Weld Bushings FEMALE S.A.E. "O-RING" to female NPT

LENZ "AN-WB" Weld Adapters are a female S.A.E. "O-Ring" connection on top or side of tank, and the female NPT connection on the inside of the tank, to save time and labor when installing components or accessories for a leak-free installation.

| MODEL | FEMALE | FEMALE | L | Х | D |
|-------------|------------------------|--------|------|------------|-------|
| NUMBER | S.A.E. | PIPE | +.03 | PILOT DIA. | DIA. |
| AN-WB-6-6 | 9/16"-18 | 3/8" | 1.41 | .808 | 1.00 |
| AN-WB-8-8 | 3⁄4"-16 | 1/2" | 1.72 | .995 | 1.125 |
| AN-WB-12-12 | 1 ¹ /16"-12 | 3/4" | 1.98 | 1.275 | 1.50 |
| AN-WB-16-16 | 15/16"-12 | 1" | 2.17 | 1.495 | 1.75 |
| AN-WB-20-20 | 15⁄8"-12 | 11/4" | 2.25 | 1.870 | 2.125 |
| AN-WB-24-24 | 17⁄8"-12 | 11/2" | 2.26 | 2.125 | 2.375 |
| AN-WB-32-32 | 2 ¹ /2"-12 | 2" | 2.41 | 3.00 | 3.25 |





"We have redesigned our Web-Site to better serve our customers and make ordering the products you need everyday more convenient."

> Visit us online @www.lenzinc.com today and see just how easy ordering your products can be.





"AN-WB" WELDBUSHINGS

